



# HOLLISTER-WHITNEY ELEVATOR CORPORATION

#1 Hollister-Whitney Parkway  
 Quincy, IL 62305  
 Phone: 217-222-0466

Fax: 217-222-0493  
 email: engineering@hollisterwhitney.com  
 www. hollisterwhitney.com

## HOLLISTER-WHITNEY VVVF LOW-SLIP HOIST MOTOR DATA OPEN DRIP PROOF

	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
1200 SRPM VERSION	5	208 / 230 / 460	2865	215T	1150	17.3 / 15.6 / 7.8	140
	7-1/2	208 / 230 / 460	3225	254T	1175	25.2 / 22.8 / 11.4	215
	10	208 / 230 / 460	4200	256T	1176	33.8 / 30.6 / 15.3	240
	12-1/2	208 / 230 / 460	4650	284T	1160	44.2 / 40 / 20	260
	15	208 / 230 / 460	5350	284T	1160	46.4 / 42 / 21	275
	20	208 / 230 / 460	6600	286T	1160	61.9 / 56 / 28	315
	25	208 / 230 / 460	7500	324T	1170	75.2 / 68 / 34	390
	30	208 / 230 / 460	8700	326T	1170	89.6 / 81.0 / 40.5	430
	40	208 / 230 / 460	12100	364T	1180	107.3 / 97 / 48.5	500
	50	208 / 230 / 460	14550	365T	1180	132.7 / 120 / 60	550
	60	208 / 230 / 460	16550	L365T	1180	155.7 / 140.8 / 70.4	600
75	208 / 230 / 460	19750	L365T	1180	193.3 / 174.8 / 87.4	700	
900 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	5	208 / 230 / 460	2750	254T	860	22.3 / 20.2 / 10.1	225
	7-1/2	208 / 230 / 460	3470	256T	860	30.3 / 27.4 / 13.7	270
	10	208 / 230 / 460	3900	284T	860	34.3 / 31 / 15.5	265
	12-1/2	208 / 230 / 460	4828	286T	860	45.8 / 41.4 / 20.7	300
	15	208 / 230 / 460	5700	286T	860	55.5 / 50.2 / 25.1	300
	20	208 / 230 / 460	7043	324T	860	67.9 / 61.4 / 30.7	340
	25	208 / 230 / 460	7850	326T	860	85.1 / 77 / 38.5	455
	30	208 / 230 / 460	9300	364T	860	92.0 / 83.2 / 41.6	700
	40	208 / 230 / 460	12511	365T	860	120.5 / 109 / 54.5	880
50	208 / 230 / 460	14892	L365T	860	149.3 / 135 / 67.5	-	
1800 SRPM VERSION	H.P.	VOLTAGE	BTU/hr.	FRAME	F.L. RPM	F.L. AMP 208V / 230V / 460V	WEIGHT (LBS.)
	5	208 / 230 / 460	2319	184T	1760	16.8 / 15.2 / 7.6	130
	7-1/2	208 / 230 / 460	3115	213T	1760	22.1 / 20 / 10	155
	10	208 / 230 / 460	3810	215T	1760	28.3 / 25.6 / 12.8	160
	12-1/2	208 / 230 / 460	4416	254T	1760	33.6 / 30.4 / 15.2	180
	15	208 / 230 / 460	5004	254T	1760	40.3 / 36.4 / 18.2	180
	20	208 / 230 / 460	5900	256T	1760	54.2 / 49 / 24.5	275
	25	208 / 230 / 460	6750	284T	1760	69.2 / 62.6 / 31.3	290
	30	208 / 230 / 460	7950	286T	1760	78.3 / 70.8 / 35.4	320
	40	208 / 230 / 460	9650	324T	1760	101.7 / 92 / 46	400
	50	208 / 230 / 460	11150	326T	1760	128.3 / 116 / 58	490
	60	208 / 230 / 460	15569	364T	1760	151.5 / 137 / 68.5	680
75	208 / 230 / 460	17539	365T	1760	187.1 / 169.2 / 84.6	840	

Open, drip proof motors by REULAND  
 All Models have 35 foot Encoder Cables  
 Standard Encoder is 2048 PPR; also available in 1024 PPR  
 Constant Torque 0-60 Hz  
 Variable Torque 60-90 Hz  
 60 Minute Duty - Inverter Duty  
 Extended End Play  
 Foot Mount Motors